

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.4 Revision Date 19.09.2022 Print Date 10.10.2022

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Sulfuric acid c(H2SO4) = 5 mol/l (10 N)

Titripur®

Product Number : 1.60315 Catalogue No. : 160315 Brand : Millipore

REACH No. : This product is a mixture. REACH Registration Number see

section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : Merck KGaA

Frankfurter Str. 250 D-64271 DARMSTADT

Telephone : +49 (0)6151 72-0 Fax : +49 6151 727780

E-mail address : TechnicalService@merckgroup.com

1.4 Emergency telephone

Emergency Phone #: +(44)-870-8200418 (CHEMTREC (GB))

+(353)-19014670 (CHEMTREC Ireland) 001-803-017-9114 (CHEMTREC India)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Corrosive to Metals (Category 1), H290 Skin corrosion (Sub-category 1A), H314 Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Millipore- 1.60315 Page 1 of 12



Signal Word Danger

Hazard statement(s)

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statement(s)

P234 Keep only in original packaging.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard statement(s)

H314 Causes severe skin burns and eye damage.

Precautionary statement(s)

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component Classification Concentration

Millipore- 1.60315 Page 2 of 12



| sulphuric acid | | | |
|----------------|-------------------|-----------------------------|--------------|
| CAS-No. | 7664-93-9 | Met. Corr. 1; Skin Corr. | >= 30 - < 50 |
| EC-No. | 231-639-5 | 1A; Eye Dam. 1; H290, | % |
| Index-No. | 016-020-00-8 | H314, H318 | |
| Registration | 01-2119458838-20- | Concentration limits: | |
| number | XXXX | >= 15 %: Skin Corr. 1A, | |
| | | H314; 5 - < 15 %: Skin | |
| | | Irrit. 2, H315; 5 - < 15 %: | |
| | | Eye Irrit. 2, H319; >= 0,3 | |
| | | %: Met. Corr. 1, H290; | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

Description of first-aid measures 4.1

General advice

First aiders need to protect themselves.

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed 4.3 No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Sulfur oxides

Millipore- 1.60315

Not combustible.

Ambient fire may liberate hazardous vapours.



Page 3 of 12

Fire may cause evolution of: Sulfur oxides

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H⁺, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Hygiene measures

Change contaminated clothing and immerse in water. Preventive skin protection Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

No metal or light-weight-metal containers.

Tightly closed. No metal containers.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 8A: Combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Millipore- 1.60315 Page 4 of 12



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact
Material: Viton®

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 120 min

Material tested:Butoject® (KCL 898)

Respiratory protection

Recommended Filter type: Filter type P2

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state liquidb) Color colorlessc) Odor odorless

d) Melting No data available

point/freezing point

Millipore- 1.60315 Page 5 of 12



e) Initial boiling point No data available and boiling range

Flammability (solid, No data available f) gas)

g) Upper/lower No data available flammability or explosive limits

h) Flash point Not applicable Autoignition No data available i) temperature

ca.338 °C -Decomposition j) temperature

at 20 °C k) pH acidic

I) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: No data available

at 20 °C soluble m) Water solubility n) Partition coefficient: No data available n-octanol/water

No data available o) Vapor pressure 1,3 g/cm3 at 20 °C p) Density No data available Relative density q) Relative vapor No data available density

No data available r) Particle characteristics

s) Explosive properties Not classified as explosive.

t) Oxidizing properties Oxidizing potential

Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

strong oxidising agent

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

A risk of explosion and/or of toxic gas formation exists with the following substances: Violent reactions possible with:

Water

Millipore- 1.60315

Alkali metals alkali compounds Ammonia



Aldehydes acetonitrile

Alkaline earth metals

alkalines

Acids

alkaline earth compounds

Metals

metal alloys

Oxides of phosphorus

phosphorus

hydrides

halogen-halogen compounds

oxyhalogenic compounds

permanganates

nitrates

Carbides

combustible substances

organic solvent

acetylidene

Nitriles

organic nitro compounds

anilines

Peroxides

picrates

nitrides

lithium silicide

iron(III) compounds

bromates

chlorates

Amines

perchlorates

hydrogen peroxide

10.4 Conditions to avoid

Strong heating (decomposition).

10.5 Incompatible materials

animal/vegetable tissues, MetalsContact with metals liberates hydrogen gas.

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

No data available

Millipore- 1.60315 Page 7 of 12



Serious eye damage/eye irritation

Mixture causes serious eye damage. Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Irritation and corrosion, Cough, Shortness of breath, Nausea, Vomiting, Diarrhea, Pain, Risk of blindness!

After inhalation of aerosols: damage to the affected mucous membranes. After skin contact: severe burns with formation of scabs. After eye contact: burns, corneal lesions. After swallowing: severe pain (risk of perforation!), nausea, vomiting and diarrhoea. After a latency period of several weeks possibly pyloric stenosis.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

sulphuric acid

Acute toxicity

LD50 Oral - Rat - male and female - 2.140 mg/kg

Remarks: (ECHA)

Inhalation: Corrosive to respiratory system.

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Extremely corrosive and destructive to tissue.

Remarks: (IUCLID)

Millipore- 1.60315 Page 8 of 12



Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative Remarks: (HSDB) Carcinogenicity No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Forms corrosive mixtures with water even if diluted. Harmful effect due to pH shift.

Millipore- 1.60315 Page 9 of 12



Endangers drinking-water supplies if allowed to enter soil or water. Discharge into the environment must be avoided. No data available

Components

sulphuric acid

Toxicity to daphnia static test EC50 - Daphnia magna (Water flea) - > 100 mg/l -

and other aquatic 48 h

invertebrates (OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) - >

100 mg/l - 72 h

(OECD Test Guideline 201)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2796 IMDG: 2796 IATA: 2796

14.2 UN proper shipping name

ADR/RID: SULPHURIC ACID IMDG: SULPHURIC ACID IATA: Sulphuric acid

14.3 Transport hazard class(es)

ADR/RID: 8 IMDG: 8 IATA: 8

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

Regulation (EU) 2019/1148 on the marketing : sulphuric acid and use of explosives precursors

Millipore- 1.60315 Page 10 of 12

A

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

| H290 | May be corrosive to metals. |
|------|--|
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture Classification procedure:

| Met. Corr.1 | H290 | Calculation method |
|--------------|------|--------------------|
| Skin Corr.1A | H314 | Calculation method |
| Eye Dam.1 | H318 | Calculation method |

Millipore- 1.60315 Page 11 of 12



The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Millipore- 1.60315 Page 12 of 12

